

NORB200128 - 12.8V200Ah

Product Features

Low voltage LFP battery system

- ⊗ High energy density, small size, light weight, no pollution;
- ⊗ 1C rate charge/discharge;
- ⊗ Match varied inverters;
- ⊗ IP20 grade, suitable for indoor;
- ⊗ 10 years design life, Stable performance, maintenance-free;



Safety Design
Much safer
More reliable.

Smart Management system
Available with,
Bluetooth, LCD


1C Charge/Discharge
Efficient charging and
discharging.

Single Management
Ultimate security and
ultra-simple O&M.

Multi-Function

Luxury lithium series batteries provide superior performance, capacities and reliability. Using state of high power cell technology, the lithium series is designed for environmentally sensitive areas that require super long cycle life capabilities.

Luxury lithium batteries are widely used in industrial, residential, commercial and private applications. The maintenance free construction and advanced design features makes the lithium series the definitive choice for a wide variety of markets. Like solar and renewable energy storage, electric vehicle, golf cart and industrial equipment, floor machines, forklifts, aerial lifts, and robotics; marine, RV, and no-idle solution; Mobility and Medical Equipment; Telecom, Broadband and Cable TV; UPS systems



Factory/Office Park/Hotel/Restaurant
Arbitraging from the TOU tariff, peak-load shifting

Mobile charger
Used as a backup power for household use

Off-grid
Multi-energy Energy system with solar, diesel generator, wind turbine, etc.

NORB200128 - 12.8V200Ah

Product Parameters

Low voltage LFP battery system

Model	NORB200128 - 12.8V200Ah
Battery Parameters	
Battery cell model	LiFePO ₄ - 200Ah
Battery capacity	2.56kWh
Dimensions(LxWxH)	330*190*190mm
Weight	21
Terminal Type	T16/Plug
Terminal Torque	8.5N*M
Case Material	Steel
BMS build-in	Yes
Efficiency – round trip	> 99.5
Self Discharge per Month	< 3%
Max parallel connectors	15
Series connections	4
Cycle life (1C, 25°C@100% DOD)	> 4000
Discharge Temperature	-20~65°C
Charge Temperature	0~65°C
Storage Temperature	-20~45°C
Bluetooth(App)	Optional
LCD Screen	Optional
Heating function	Optional
Voltage Window	10.8~14.6V
Recommend Charge Voltage	14.0V
Max Charge Voltage	14.6V
Recommend Charge current	40A
Max continuous charge current	200A
Recommend Discharge voltage	11.2V
Max Discharging Voltage	10.8V
Max Continuous Discharge current	200A
Peak Discharge Current	220A
Communication	Bluetooth

* The system will be derated when the ambient temperature exceeds 45°C.

** The system will be derated when the altitude is between 2000 and 3000m.

Certifications

System: CE(IEC61000,IEC62619,IEC62477),UN3480, UKCA ;

Note: Product specifications are subject to change without any prior notice as per regular modifications made by company.


Constant Current Discharge Data (Amperes @ 25°C)

Discharge Time	1h	2h	3h	4h	5h	10h	20h
Cut off voltage (10.8V)	200A	100A	66A	50A	40A	20A	10A


Constant Watts Discharge Data (Amperes @ 25°C)

Discharge Time	1h	2h	3h	4h	5h	10h	20h
Cut off voltage (10.8V)	2560W	1280W	850W	640W	512W	256W	128W


Discharge characteristics (25°C)




Different temperature Discharge curve (0.5C)



Discharge DOD discharge cycle life curve (0.2C, 25°C)



State of charge curve (0.5C, 25°C)



Note 1: Please always refer to the latest edition of our technical manual that published on our website to ensure safe and efficient operation.

Note 2: When make parallel connection, please full discharge batteries, then recharge after parallel connected; when series connect, please keep batteries with same remain capacity.